

Pride[®] LX

The LX offers standard features necessary to meet the demands of daily life while delivering easy portability. The LX combines rear anti-tip wheels for stable outdoor performance with a compact frame for smooth indoor manoeuvring. With additional features like clothing guards and a length-adjustable controller bracket, the LX is the ultimate economical folding power chair.



Pride[®] LX
shown in Silver with
Sling-back seat, swing-away
footrests and VSI controller

32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL
(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk

Pride[®]
Mobility Products Ltd.

SPECIFICATIONS

Weight capacity	113 kg (18 Stone)
Maximum speed	Up to 6 km/h (4 mph)
Ground clearance	11 cm (4.5")
Turning radius	84 cm (33")
Overall length	109 cm (43")
Overall width	65 cm (25.5")
Folded width	32 cm (12.5")
Wheels	Drive: 33 cm (13")
Anti-tips	5 cm (1.9") rear-mounted, solid
Castors	20 cm (8") solid
Suspension	Limited
Drive train	2-motor, rear-wheel drive
Braking system	Intelligent braking (electronic, regenerative disc brakes)
Standard electronics	50 amp, PG VSI
Specialty controls	N/A
Battery charger	Off-board, 5 amp
Battery requirements	(2) 12 volt deep cycle
Battery size	30 amp
Battery weight	11 kg (24.5 lbs.) each
Base weight	38 kg (83 lbs.)
Standard seat weight	N/A
Std. seat dimensions	41 cm x 46 cm (16" x 18")
Warranty	1-year warranty on electronics; 2-year warranty on motor; Lifetime-limited warranty on frame

COLOUR CHOICES



Silver

FEATURES

- A sturdy foldable frame
- Clothing guards
- Swing-away footrests with heel loops
- Fold-down back
- Length-adjustable controller bracket
- Push handles
- Removable rear anti-tip wheels
- Tool kit
- Lap belt
- Solid tyres
- Flip-up, height adjustable armrests

OPTIONS

- Elevating leg rests
- Kerb climber
- Attendant control
- Dual control

32 Wedgwood Road, Bicester, Oxfordshire OX26 4UL
(Tel) 01869 324 600 • (Fax) 01869 323 070 • www.pridemobility.co.uk

The information contained herein is correct at the time of publication; due to the manufacturers commitment to constant improvement and development, they reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressure, ambient temperature, and the gradient and surface of the road or pavement.



PRIDE[®]
PERFORMANCE MOBILITY
— LIVE YOUR BEST™ —